

Dark Grey PVC-P Spiral Hose Datasheet

Product Code: RC07-I-122

Product Description

Dark grey PVC-P spiral hose, reinforced with an anti-shock rigid PVC spiral.

Technical Specification

Ø INT.	Min Wall Thickness	Max Wall Thickness	Weight	Vacuum	Bending	Coil Length	Volume
mm/inch	mm	mm	g/m	m H ² O	mm	m	m ³
25	0.8	2.7	160	2.5	30	50	0.073
27	0.8	2.7	170	2.5	30	50	0.082
30	0.8	2.8	200	2.5	40	50	0.115
31.8	0.8	2.8	210	2	40	50	0.121
35	0.8	2.9	220	2	40	50	0.131
38.1	0.8	3.1	270	2	50	50	0.142
39	0.8	3.1	270	2	50	50	0.145
40*	0.8	3.1	280	2	50	50	0.177
45	0.8	3.4	350	2	60	50	0.199
50*	0.9	3.7	430	2	60	50	0.248
51.5	0.9	3.7	440	2	60	50	0.254
50.8	0.9	3.7	440	2	60	50	0.251
55	0.9	3.7	470	2	70	50	0.270
60*	0.9	3.7	510	1.6	80	50	0.388
63.5	0.9	3.7	540	1.6	80	50	0.408
65	0.9	3.7	550	1.6	80	50	0.417
70	1	3.9	590	1.5	90	50	0.448
75	1	4	650	1.5	90	50	0.598
76.2*	1	4	660	1.5	100	50	0.606
77.7	1	4	670	1.5	100	50	0.617
80*	1	4.6	790	1.5	100	50	0.642
90	1	4.6	890	1.4	110	30	0.429
100*	1	4.9	1000	1.3	130	30	0.632
102*	1	4.9	1020	1.3	130	30	0.644
103.5	1	4.9	1030	1.3	130	30	0.653

The technical data here reported has been measured at 23°C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Technical Specification

Ø INT.	Min Wall Thickness	Max Wall Thickness	Weight	Vacuum	Bending	Coil Length	Volume
mm/inch	mm	mm	g/m	m H ² O	mm	m	m ³
105	1	5	1070	1.2	130	30	0.662
110	1	5.2	1160	1.2	140	30	0.694
120*	1	5.2	1260	1	150	30	0.751
125	1	5.2	1310	1	150	30	0.780
127	1	5.2	1330	1	150	30	0.791
130	1	5.2	1360	0.9	160	30	0.809
140	1	5.2	1460	0.9	170	30	10155
151.5*	1.1	5.6	1690	0.8	180	20	0.937
152.4	1.1	5.6	1700	0.8	180	20	0.942
160	1.1	6.3	1860	0.7	190	20	0.884
180	1.1	6.3	2090	0.4	210	20	0.986
200*	1.1	6.5	2280	0.4	230	20	1.636
203.2	1.1	6.5	2310	0.4	230	20	1.660
250*	1.2	7.3	3390	0.4	270	10	1.355
300*	1.2	7.4	4140	0.3	300	10	1.612

The technical data here reported has been measured at 23°C with 50% humidity.

**Sizes highlighted in green are available from stock.*

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.