

Rubber Threshold Ramps Datasheet

Product Code: RC1143

Product Description

The Rubber threshold ramps from The Rubber Company are crafted using 100% recycled rubber, ensuring a seamless gradient for disabled access. These ramps boast a high load capacity and are versatile for indoor and outdoor use. Known for their strength, durability, and non-slip surface, these ramps are straightforward to install and require minimal maintenance. Please also note, width measurements specified include sloped edges.

Size Specifications

Property	Value
Length (mm)	210 - 635
Width (mm)	900 - 1105
Max. Load Height (mm)	100
Weight (kg)	4.20 - 23.60
Capacity (kg)	1000

Key Features

- Supports up to **1000kg weight**, ideal for wheelchairs, walkers, scooters, and pedestrians
- **Ready to use** without installation—simply rest in place
- **Weatherproof** design suitable for home, workplace, or outdoor use
- **Anti-slip surface** ensures excellent traction
- Crafted from **100% recycled rubber** compound
- Easily **adjustable width** with a knife or saw
- **Bevelled edges** minimise trip hazards
- Available as singles in widths of 1105mm or 900mm based on chosen height
- Explore our complete Rubber Threshold Ramps range for higher heights and more options

Please be aware that the natural odour of rubber dissipates within a few days when exposed to fresh air. To speed this process, wipe the surface with a damp cloth containing washing up liquid.



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Size Variations

Thicknesses	Values
1"/25mm	Length (mm): 210
	Width (mm): 1105
	Usable Width (mm): 900
	Weight (kg): 4.2
	Capacity (kg): 1000
1.5"/38mm	Length (mm): 320
	Width (mm): 1105
	Usable Width (mm): 900
	Weight (kg): 8.6
	Capacity (kg): 1000
2"/50mm	Length (mm): 410
	Width (mm): 1105
	Usable Width (mm): 900
	Weight (kg): 12.3
	Capacity (kg): 1000
2.5"/65mm	Length (mm): 420
	Width (mm): 1105
	Usable Width (mm): 900
	Weight (kg): 14.1
	Capacity (kg): 1000
3"/76mm	Length (mm): 460
	Width (mm): 900
	Usable Width (mm): 700
	Weight (kg): 13.20
	Capacity (kg): 1000
3.5"/90mm	Length (mm): 540
	Width (mm): 900
	Usable Width (mm): 700
	Weight (kg): 17.3
	Capacity (kg): 1000



Manufacturers • Designers • Distributors

Experts in
Rubber

Size Variations

Thicknesses	Values
4"/100mm	Length (mm): 635
	Width (mm): 900
	Usable Width (mm): 700
	Weight (kg): 23.6
	Capacity (kg): 1000

Technical Data

Thicknesses	Values
Capacity (kg)	1000
Length (mm)	210 - 635
Max Load Height	100
Min. Load Height (mm)	25
Weight (kg)	4.20 - 23.60
Width (mm)	900 - 1105
One Year Warranty	Yes
Easy to Fit	Yes
Electric Wheelchair	Yes
Manual Wheelchair	Yes
Mobility Scooter Friendly	Yes
Leave Outside	Yes