

Experts in **Rubber**

Manufacturers · Designers · Distributors

Rubber Threshold Ramps Datasheet


Product Code: RC1144

Product Description

The Rubber Company's rubber threshold ramps are designed with a 1:6 gradient for smooth accessibility. These ramps offer a high load capacity, suitable for both indoor and outdoor use. Known for their strength, durability, and non-slip attributes, these ramps are straightforward to install and maintain. They are available for purchase as singles or in pairs, each ramp measuring 400mm in width. Typically, wheelchair or scooter users may require at least two of these ramps for optimal use.

Size Specifications

Property	Value
Length (mm)	685.8 - 1066.8
Width (mm)	400
Height (mm)	114.3 - 177.8
Weight Per Ramp (kg)	10.5 - 24.5
Capacity (kg)	1000





Key Features

- Capable of bearing a weight of up to 1000kg
- Features an **anti-slip surface** for secure usage
- Suitable for both indoor and outdoor environments, designed for outdoor placement
- Crafted from a 100% recycled rubber compound
- Convenient "rest and go" functionality—simply slide up to the kerb and start loading
- For lower heights, explore our complete selection of Rubber Threshold Ramps
- Please note: These ramps are typically left in place due to their weight
- As these ramps are made of rubber, you can adjust their width using a saw

Please be aware that the natural odour of rubber dissipates within a few days when exposed to fresh air. To speed this process, wipe the surface with a damp cloth containing washing up liquid.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.





 $\textit{Manufacturers} \cdot \textit{Designers} \cdot \textit{Distributors}$

Size Variations

Thicknesses	Values
4.5"/114.3mm	Length (mm): 685.8
	Width (mm): 400
	Weight per ramp (kg): 10.5
	Capacity (kg): 1000
5″/127mm	Length (mm): 762
	Width (mm): 400
	Weight per ramp (kg): 12.6
	Capacity (kg): 1000
5.5"/139.7mm	Length (mm): 838.2
	Width (mm): 400
	Weight per ramp (kg): 14.8
	Capacity (kg): 1000
6"/152.4mm	Length (mm): 914.4
	Width (mm): 400
	Weight per ramp (kg): 17.20
	Capacity (kg): 1000
6.5"/165.1mm	Length (mm): 990.6
	Width (mm): 400
	Weight per ramp (kg): 19.80
	Capacity (kg): 1000
7"/177.8mm	Length (mm): 1066.8
	Width (mm): 400
	Weight per ramp (kg): 24.5
	Capacity (kg): 1000





Manufacturers · Designers · Distributors

Technical Data

Thicknesses	Values
Capacity (kg)	1000
Height (mm)	114.3 - 177.8
Height (inches)	4.5 - 7"
Length (mm)	685.8 - 1066.8
Weight per Ramp (kg)	10.5 - 24.5
Width (mm)	400
Width (ins)	15.74"
One Year Warranty	Yes
Easy to Fit	Yes
Electric Wheelchair	Yes
Manual Wheelchair	Yes
Mobility Scooter Friendly	Yes
Leave Outside	Yes