

White FDA Abrasion Resistant Sheeting

Product Code: RC0305

Issue Date: 13th June 2014

Vulcanised rubber sheets made from the high quality Natural Rubber & Styrene Butadiene Rubber, containing additives such as antioxidants, carbon black and mineral fillers, process aids and chemicals for vulcanisation.

Physical & Chemical Properties

Property	Value
State:	Vulcanised Rubber Sheet
Solubility in Water:	Insoluble
Boiling Point (°C)	Not Applicable
Working Temperature Range (°C)	-30°C to +70°C
Specific Gravity	0.98 (gm/cc)
Tensile Strength	240 (kg/cm ²)
Elongation	810 (%)
Hardness	38 ± 5 (Shore A)
Appearance	Solid Sheet

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Hazard Identification

RISK None under normal operating conditions

SAFETY None under normal operating conditions

ACUTE HEALTH EFFECTS AND FIRST AID MEASURES (FAM)

EYE CARE: Although the material is not thought to be an irritant, direct contact with the eye may produce transient discomfort characterized by tearing or conjunctival redness.

FAM: If this product comes in contact with eyes, wash out immediately with water. If irritation continues, seek medical attention.

SKIN CARE: The material does not produce adverse health effects or skin irritation following contact. Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

FAM: If skin or hair contact occurs, Flush skin and hair with running water (and soap if available), Seek medical attention in event of irritation.

SWALLOWING

Ingestion is not thought to produce harmful effects, the material may still be damaging to the health of the individual, following ingestion. It may cause discomfort in the intestinal tract.

FAM: Consult doctor.

INHALING:

The material does not produce adverse health effects or irritation of the respiratory tract following contact. Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

FAM: In case of discomfort, consult doctor.

PROLONGED HEALTH EFFECTS

The additives are mixed in the rubber and do not present a hazard during handling at room temperature.

FAM: In case of prolonged discomfort, doctors are advised to treat the symptoms.

Fire Fighting Measures

EXTINGUISHING MEDIA:

Carbon Dioxide

Dry Chemical Powder

Water Spray or Fog - Large Fires Only

Foam

FIRE FIGHTING

Water breathing apparatus plus protective gloves

Alert Fire Brigade and tell them location and nature of hazard

Use water delivered as a fine spray to control fire and cool adjacent area.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

FIRE / EXPLOSION HAZARD

Non combustible

Not considered a significant fire risk, however product may burn.

Handling and Storage

SUITABLE CONTAINER

No restriction on the type of containers. Packing as recommended by manufacturer.

Check all material is clearly labeled.

STORAGE INCOMPATIBILITY

No known incompatibility with normal range of industrial materials.

STORAGE REQUIREMENTS

Special storage precautions not required.

TRANSPORTATION

No restrictions.

Stability and Reactivity

Chemical Stability

Stable at normal temperature and storage condition.

Conditions to Avoid

Overheating

Incompatibility with other materials

No specific information is available, however strong oxidizing or reducing agents which are generally not compatible with the sheets.

Hazardous Decomposition Products

Fumes produced when heated to decomposition temperatures may contain styrene, carbon monoxide, carbon-dioxide, sulfur-di-oxide, aromatic and aliphatic hydrocarbons and nitrogenous products.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



Manufacturers • Designers • Distributors

Experts in
Rubber

Disposal Considerations

Preferred options for disposal are (1) recycling, (2) incineration with energy recovery, and (3) landfill. The high fuel value of this product makes option 2 very desirable for material that cannot be recycled, but incinerator must be capable of scrubbing out acidic combustion products. Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial and local regulations.

Transportation Information

Shipping Information

DOT

Proper Shipping Name: not regulated

Hazards Class: not regulated

Regulatory Information

TSCA Inventory Status: This product and all components are listed on the EPA Toxic Substances Control Act Inventory.

Export Notification Status: This product does not contain any components subject to export notification requirements.

Important Note:

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. This information is obtained from various sources including the manufacturer and other third party sources. The safety data sheet only describes the products in aspect to their safety requirements.



ISO
9001 : 2015
REGISTERED



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.