

## Acrylic Tissue Tape Datasheet

Product Code: RC13-PSA-8441

### Food Contact Information

Based on supplier information the raw materials used in producing the adhesive tape conform to the compositional requirements of FDA 175.105 for indirect food contact. Additional to this compliance there should also be a functional barrier between adhesive and the food. Such functional barrier and determination of suitability are the responsibility of the customer.

### Technical Specification

| Property                                   | Value                                                            |
|--------------------------------------------|------------------------------------------------------------------|
| Material                                   | Acrylic Tissue Tape                                              |
| Available Thicknesses                      | 115 Micron                                                       |
| Liner                                      | 80g Brown Silconised Release Paper                               |
| Carrier                                    | 13g Tissue                                                       |
| Adhesive                                   | Acrylic based with 45gsm on both open and closed sides           |
| Total Thickness                            | 115 micron                                                       |
| Peel Adhesion to Steel (24-hour dwell)     | protected 650 N/M                                                |
| Shear adhesion to steel:                   | protected 50 hours open 50 hours                                 |
| Service temperature range:                 | -10°C to 180°C                                                   |
| Recommended application temperature range: | 5°C to 60°C                                                      |
| Continous operating temperature range:     | 25°C                                                             |
| Shelf Life:                                | Recommended 12 months from supply                                |
| Widths:                                    | 3mm, 6mm, 9mm, 12mm, 25mm, 50mm, 1000mm (other widths available) |
| Lengths:                                   | 10m, 25m, 50m, 100m, 250m (other lengths available)              |



**ISO  
9001 : 2015  
REGISTERED**

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.