



TICO® VHT/CL - Ultra High Temp Clamp Strip Datasheet Product Code: RC1170

Product Description

TICO® VHT/CL - Ultra High Temperature Clamp Strips isolate vibration between pipework and hangers. They are primarily manufactured from silicone rubber and able to withstand temperatures up to +300°C continuous, +350°C intermittent. The material prevents electrolytic action between dissimilar materials. Featuring a raised shoulder design for positive location, they are pliable and easy to cut, supplied in a yellow colour.

Technical Specification

Property	Test Method	Value	
Hardness	ISO 48	60° ± 10° (IRHD)	
Density	ISO 2781	1.15g/cm³	
Coefficient of Friction (TORTUS)	ISO 37	4.0 Mpa minimum	
	ISO 37	300% minimum	
Temperature Range	-	-60°C to +300°C	
Compliance BS EN ISO 9002		Acceptable	

Heat Ageing @ 300°C

Time (Hours)	Shore A Hardness° (ASTM D2240)	Density g/cm³ (ASTM D297)	
0	55	1.155	
24	58	1.161	
48	68	1.170	
72	67	1.169	
168	76	1.181	





The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



Experts in Rubber


Manufacturers · Designers · Distributors

UV Exposure (ASTM G4)

Time (Hours)		Density g/cm³ (ASTM D297)	Colour Change
168	No change	No change	Minor colour change

Water Immersion

Time (Hours)	Mass Increase
24 hours @ 23°C (ASTM D471)	+0.13%



Dimensions

Product Code	Base Thickness (A)	Clip Width (B)	Recess Depth (R)	Wall Width (W)
RC1170-35	2mm (0.08")	35mm (1.38")	2mm (0.08")	5mm (0.20")
RC1170-45	2mm (0.08")	45mm (1.77")	2mm (0.08")	5mm (0.20")
RC1170-55	2mm (0.08")	55mm (2.17")	2mm (0.08")	5mm (0.20")
RC1170-65	2mm (0.08")	65mm (2.56")	2mm (0.08")	5mm (0.20")
RC1170-75	2mm (0.08")	75mm (2.95")	2mm (0.08")	5mm (0.20")
RC1170-85	2mm (0.08")	85mm (3.35")	2mm (0.08")	5mm (0.20")
RC1170-95	2mm (0.08")	95mm (3.74")	2mm (0.08")	5mm (0.20")
RC1170-105	2mm (0.08")	105mm (4.13")	2mm (0.08")	5mm (0.20")
RC1170-115	2mm (0.08")	115mm (4.53")	2mm (0.08")	5mm (0.20")





The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.