

FlexiRidge Durable Ribbed Matting Datasheet

Product Code: RC04165

Product Description

FlexiRidge durable ribbed PVC matting is a high-quality flooring solution designed for hard-wearing industrial applications. Its dense construction provides vibration and acoustic-dampening properties, while also offering impact protection to reduce damage from dropped items and tools. The ribbed channels help to quickly disperse liquid, dirt, and debris away from the walking surface.



Technical Specification

Property	Value
Material	Flexible Polyvinyl Chloride (PVC)
Chemical Resistance	Resistant to most acids, alkalines and oils
Fire Resistance	EN 13501-1: 2007-Bfl-S1
Temperature Range	-23°C to +60°C
UV Resistance	Resistant to PVC degradation
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%
Environment	100% recyclable
Size	1m x 20m roll
Thickness	2.8mm
Weight	2.45kg/m ²
Colour	Dark Grey



**ISO
9001 : 2015
REGISTERED**

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



Manufacturers • Designers • Distributors

Experts in
Rubber

Installation & Maintenance

Supplied in a 1m x 20m roll, Flexiridge is easy to lay and cut to size using heavy-duty scissors.

- Loose lay, no permanent fixtures required.
- Holes can be cut to accommodate objects.
- Contours to uneven floors.

FlexiRidge is quick and easy to clean. simply wipe clean or vacuum. For convenience, the matting can also be rolled for transport and storage.



ISO
9001 : 2015
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.