

Silicone Sponge Sheeting

Product Code: RC02101

Key Features

- Meets the flammability requirements of FAR 25/JAR25/CS 25 Appendix F, Part 1 (a)(1)(iv) and (a)(1)(v) horizontal flammability
- Close cell structure with low water absorption
- Suitable where a soft, easily pliable rubber is required
- Available plain or with adhesive backing
- Performs at temperatures from -60° C to +230° C, +250° C intermittently

Attributes



High Temperature



Weather-Resistant



Chemical-Resistant

Available in:



Full Rolls



Cut Strips



Bespoke Gaskets

Technical Data

Property	Test Method	Values			
Grade	-	P10	P16 (TRC16)*	P24	P33
Density	ISO 845 ASTM D3574	200 kg/m ³	250kg/m ³	400kg/m ³	550 kg/m ³
Hardness (Shore 00)	ASTM D2240	35° ± 5°	42° ± 5°	65° ± 5°	80° ± 5°
Hardness (Shore A)	ASTM D2240	<5	5	17	30
Tensile Strength	ISO 1798 ASTM D412	0.6 MPa	0.6 MPa	0.75 MPa	2.0 MPa
Elongation at Break	ISO 1798 ASTM D412	140 %	145 %	120 %	130 %
Compression Stress 40 % Strain	ISO 3386 Part 1, 2 ASTM D1056	50 kPa	90 kPa	165 kPa	470 kPa
Compression Set (50%, 22 h @ 70° C, 24 h recovery)	ISO 1856	15 %	12 %	10 %	9.5 %
Compression Set (50%, 22 h @ 100° C, 24 h recovery)	ISO 1856	18 %	14.5 %	12 %	12 %
Water Absorption	ASTM D1056	<5 %	<5 %	<5 %	2 %
Temperature Range	-	-60° C to +230° C (intermittent +250° C)			

*TRC16 is shown on our sample card.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E sales@therubbercompany.com

W www.therubbercompany.com

T +44 (0) 1794 513 184

The Rubber Company Limited - Registered in England and Wales
Company Number - 08350831 | VAT Number - GB 156 8355 80



Standard Sizes

P16 (TRC16) - Black, White, Red Oxide

Sheet Thickness	Sheet Size	Backing
1.5mm	1m x 1m	Plain / Adhesive-Backed
2mm	1m x 1m	Plain / Adhesive-Backed
3mm	1m x 1m	Plain / Adhesive-Backed
4mm	1m x 1m	Plain / Adhesive-Backed
5mm	1m x 1m	Plain / Adhesive-Backed
6mm	1m x 1m	Plain / Adhesive-Backed
8mm	1m x 1m	Plain / Adhesive-Backed
10mm	1m x 1m	Plain / Adhesive-Backed
12mm	1m x 1m	Plain / Adhesive-Backed
15mm	1m x 1m	Plain / Adhesive-Backed
20mm	1m x 1m	Plain / Adhesive-Backed
25mm	1m x 1m	Plain / Adhesive-Backed
30mm	1m x 1m	Plain / Adhesive-Backed

P24 - Black, White

Sheet Thickness	Sheet Size	Backing
1.6mm	1m x 1m	Plain / Adhesive-Backed
2mm	1m x 1m	Plain / Adhesive-Backed
3mm	1m x 1m	Plain / Adhesive-Backed
4mm	1m x 1m	Plain / Adhesive-Backed
5mm	1m x 1m	Plain / Adhesive-Backed
6mm	1m x 1m	Plain / Adhesive-Backed
8mm	1m x 1m	Plain / Adhesive-Backed
10mm	1m x 1m	Plain / Adhesive-Backed
12mm	1m x 1m	Plain / Adhesive-Backed
15mm	1m x 1m	Plain / Adhesive-Backed

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Standard Sizes

P33 - White

Sheet Thickness	Sheet Size	Backing
2mm	1m x 1m	Plain / Adhesive-Backed
3mm	1m x 1m	Plain / Adhesive-Backed
4mm	1m x 1m	Plain / Adhesive-Backed
5mm	1m x 1m	Plain / Adhesive-Backed
6mm	1m x 1m	Plain / Adhesive-Backed

Approvals



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.