

## Anti-Static Mats

Product Code: RC0319

### Key Features

- Conforms to BS IEC 61340-5-1
- Highly flexible
- Excellent lay flat properties but easily studded if required for custom fits
- High resistance to oil
- High temperature resistance
- Excellent abrasion resistance
- No curling or deformation

### Attributes



Durable



Abrasion-Resistant



High Temperature



### Technical Data

Property	Test Method	Value
Compound	-	Styrene Butadiene Rubber
Density	ASTM D1298	1.3 g/cm <sup>2</sup>
Tensile Strength	ASMT D412	8 MPa
Elongation at Break	ASTM D412	350 %
Abrasion Resistance	DIN 53516	85 mm <sup>3</sup>
Tear Strength	ASTM D624	45 Nmm <sup>-1</sup> ± 5
Surface Resistivity - Black	ASTM F150	10 <sup>3</sup> - 10 <sup>5</sup>
Surface Resistivity - Colour	ASTM F150	10 <sup>7</sup> - 10 <sup>9</sup>
Standard Roll Size	-	1.2m x 10m x 2mm

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.