

Anti-Slip Waterproof Tape

Product Code: RC3405

Key Features

- Waterproof, non-abrasive anti-slip surface
- Embossed PVC texture for effective grip
- Comfortable for barefoot use
- Easy to clean and hygienic
- No grit shedding or surface breakdown
- Kind to skin, clothing and equipment
- Suitable for wet areas and kitchens

Attributes



Anti-Slip



Durable



Watertight



Technical Data

Property	Test Method	Value
Back Carrier	Calipers	0.65mm PVC
Type of Adhesive	-	Modified Solvent Acrylic
Adhesive Thickness	-	0.06mm
Total Thickness	-	0.79mm
Initial Tack	PSTC-16	3.2 kg/25.4mm
Holding Power	PSTC-7	> 24 Hour
Peel Adhesion	FINAT FTMI 180°	18.8 N/20mm
Tensile Strength	Lloyd, 500N Load Cell	< 200 N/20mm
Peel Adhesion	PSTC-1	1.4 kg/25.4mm
Tensile Strength (MD)	ASTM D882A:1997	120.4 kgf/cm ²
Elongation at Break	ASTM D882A:1997	199 %
Tear Resistance (MD)	ASTM D1004:1994 Die C	5.36 kgf/cm ²
Dimensional Stability (MD)	ASTM D1593:1994	0 %

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Technical Data Continued

Property	Test Method	Value
Temperature Range	-	-30° C to +70° C
Maximum Size of Roll Production	-	1194mm x 100m

Coefficient of Friction Data

Test Method	Dry Surface	Wet Surface
EN 16165:2021 Pendulum Test Value (PTV)	1.06	0.31
DIN 51097	Category B	Category B

Light Reflective Values

Colour	RAL	Average LRV	Range
Black	7021	4	1
Beige	1035	37.5	2
Grey	7037	10	2
Transparent	Transparent	56	2
White	9003	52	4

Approvals



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.