

Conformable Anti-Slip Safety Grip Tape

Product Code: RC3406

Key Features

- Durable, coarse anti-slip surface
- Moulds to textured metal like durbar plate, chequer plate or diamond tread
- Aluminium foil backing so conforms to uneven surfaces
- Flame retardant, Class O rated
- 1.12mm thick for long-lasting grip
- Available in rolls 19mm to 1168mm wide

Attributes



Anti-Slip



Durable



Flame Retardant



Technical Data

Property	Test Method	Value
Back Carrier	Calipers	0.075mm Soft Aluminium
Total Applied Thickness	Calipers	1.12mm
Type of Adhesive	-	Solvent Acrylic
Peel Adhesion	FINAT FTMI 180°C	17.7 N/25mm
Tensile Strength	Lloyd, 500N Load Cell	148.63 N/25mm
Fire Retardancy	CAA / FAA Spec 8	Pass
Mineral Type	-	Aluminium Oxide
Adhesion to Steel	PSTC-4	2000 g/25.4mm ²
Temperature Range	-	-40° C to +160° C
Maximum Size of Roll Production	-	980mm x 100m
Colour	-	Black, Yellow, Black / Yellow Hazard, Orange, White
Coefficient of Friction - Dry Surface	Pendulum EN 16165:2021	0.99 PTV
Coefficient of Friction - Wet Surface	Pendulum EN 16165:2021	0.75 PTV

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Light Reflective Values

Colour	RAL	Average LRV	Range
Black	9004	0	0
Yellow	1023	37.5	3
Black / Yellow Hazard	9017 / 1003	0 / 43.5	0 / 4
Orange	2004	18.3	3
White	9003	72.3	1

Approvals



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.