

Interlocking Rubber Cow Matting

Product Code: RC04113

Key Features

- Anti-slip cobbled surface for safety
- Anti-fatigue comfort reduces joint and ligament strain
- Easy interlocking installation for large areas
- Low maintenance and simple to clean
- Heavy-duty design for cattle and livestock
- Supports increased milk and meat production
- Versatile for barns, stables, and pens
- Unique recessed hollowed cellular back for drainage

Attributes



Anti-Slip



Durable



Low Maintenance



Technical Data

Property	Value
Compound	Natural rubber / styrene-butadiene rubber blend
Hardness (Shore A)	65°
Density	1.4 g/cm ³
Tensile Strength	6 MPa
Elongation (min)	300 %
Abrasion Resistance	200mm ³
Working Temperature Range	-20° C to +70° C
Colour	Black

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Standard Size

Stock Size	Weight
1.15m x 1.83m x 28mm (Interlocking long side)	42 kg
1.2m x 1.83m x 25mm (Straight edge)	40 kg

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.