

Fine Ribbed Rubber Matting

Product Code: RC04117

Key Features

- High-quality ribbed design
- Good level of grip in both dry and wet environments
- Resists curling and warping while in use
- Creates a barrier on cold flooring substrates
- Good sound dampening properties
- Suitable for interior and exterior applications
- Easily cut to shape

Attributes



Anti-Slip



Durable



Low Maintenance



Technical Data

Property	Value	
	Standard	Premium
Compound	Styrene-Butadiene Rubber / Natural Rubber	
Hardness (Shore A)	65° - 75°	70°
Density	1.5 g/cm ²	1.5 g/cm ²
Tensile Strength	4.0 MPa	3.0 MPa
Elongation at Break (min)	130 %	150 %
Abrasion Resistance	300 mm ³	300 mm ³
Working Temperature Range	-20° C to +70° C	-20° C to +70° C
Colour	Black	Black, Blue, Green, Grey, Red

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Standard Sizes

Stock Size	Thickness
10m x 90cm	3mm
10m x 1m	3mm
10m x 1.2m	3mm
10m x 1m	4.5mm
10m x 1.2m	4.5mm
10m x 1m	6mm
10m x 1.2m	6mm

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.