

ToughGrip Slip Resistant Matting

Product Code: RC04141

Key Features

- Designed to withstand all kinds of liquids
- Diamond cut pattern
- Two layer open-grid construction
- Proven anti-fatigue properties
- Certified slip resistant (DIN 51130: R11, ASTM 1677: 1.0/0.9)
- Excellent drainage (DIN 51130: V10)
- Chemical, oil and acid resistant
- Contours to uneven surfaces

Attributes



Anti-Slip



Anti-Fatigue



Oil-Resistant



Technical Data


Property	Value
Compound	Polyvinyl chloride
Acoustic Insulation	Excellent sound absorption
Anti-fatigue	10% reduction in fatigue
Chemical Resistance	Resistant to most acids, alkalines and oils
Electrical Resistance	BS 2782: Part 2 Method 230A Insulation resistance > 2000M Ω Electric strength = 12,600 volts
Fire Resistance	EN ISO 13501-1:2007-Cfl-SI
Temperature Range	-23° C to +60° C
UV Resistance	Resistant to PVC degradation
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%
Hygiene	Naturally resistant to bacteria growth
Environment	100% recyclable

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.


Standard Size

Stock Size	Thickness	Weight
10m x 0.6m	15mm	7.6 kg/m ²
10m x 0.91m	15mm	7.6 kg/m ²
10m x 1.22m	15mm	7.6 kg/m ²


Colour Options




Black



Red



Blue



Black with Yellow Edging

Installation

Supplied in 10m rolls, ToughGrip is quick and easy to install.

- Loose lay, no permanent fixtures required
- Easy to cut to size
- Holes can be cut to accommodate pipes
- Contours to uneven surfaces

Cleaning & Maintenance

Keeping ToughGrip matting clean is a quick and easy job.

- Dirt and debris will naturally fall away from the surface of the matting
- Easy to move, simply roll or lift to clean
- No special cleaning tools required
- Can be washed down with a high pressure hose

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Approvals



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.