

# RubbaGrit Non-Slip Matting

Product Code: RC04156

## Key Features

- Mineral coated grit top finish
- Outstanding anti-slip properties, in dry and wet conditions
- Conforms to slip resistance test – DIN 51130 Category R11
- Good tear and puncture resistance
- Highly flexible to contour to uneven surfaces
- Oil resistant for heavy industrial areas
- Easy to cut to shape

## Attributes



Anti-Fatigue



Anti-Slip



Low Maintenance



## Technical Data

Properties	Test Method	Data
Compound	-	Nitrile Butadiene Rubber
Hardness (Shore A)	ASTM D2240	60° ± 5°
Density (Specific Gravity)	ASTM D1298	1.3 ± 0.05
Tensile Strength	ASTM D412	5 MPa ± 1 MPa
Elongation at Break	ASTM D412	300 % ± 50 %
Tear Strength	ASTM D624	35 N/mm ± 5 N/mm
Heat Resistance (70 h @ 70° C)	ASTM D573	No visual damage

## Standard Size

Stock Size	Thickness	Weight
1.2m x 10m	3mm	2.6 kg/m <sup>2</sup>

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

## Approvals



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.