

Diamond Interlocking Rubber Matting

Product Code: RC04178

Key Features

- Heavy duty, interlocking rubber matting
- Anti-slip diamond textured surface
- Easily connects to cover large areas
- Bevelled edges for wheelchairs, trolleys, and reducing trip hazards
- Quick and easy to install
- Suitable for dry areas

Attributes



Anti-Slip



Anti-Fatigue



Durable



Technical Data

Property	Value
Compound	Natural and recycled rubber
Hardness (Shore A)	55°
Tensile Strength	3 - 3.5 MPa
DIN Abrasion Loss (mm ²)	200 % - 250 %
Elongation at Break	200 % - 250 %
Temperature Range	-20° C to +130° C
Slip Resistance	Slip resistance surface Level 2
Wear Resistance	Wear resistant surface to Level 2, suitable for medium to high use
Anti-Fatigue	Anti-fatigue protection to Level 3
Impact Resistance	Impact resistant
Connectable	Mats are connectable and can join together
Wheeled Area	Suitable for use by wheeled trolleys
Dry Area	Suitable for use in dry areas

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Standard Sizes

Size	Thickness	Weight
71cm x 78cm	14mm	4.4 kg

Approvals



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.