

Coarse Safety Grip Tape

Product Code: RC3402

Key Features

- 36 grit aluminium oxide coarse surface
- Superior traction in demanding environments
- Designed for construction and heavy-duty sites
- Suitable for areas exposed to constant coverage of dirt or water
- Total thickness: 1.02mm
- Deep grit channels aid drainage and prevent clogging
- Available in widths from 19mm to 1168mm
- Ideal for industrial and outdoor applications

Attributes



Anti-Slip



Durable



High Strength



Technical Data

| Property | Test Method | Value |
|-------------------------|-------------|----------------------------|
| Back Carrier | Calipers | 0.1mm Polyvinyl Chloride |
| Total Applied Thickness | Calipers | 1.02mm |
| Type of Adhesive | - | Solvent Acrylic |
| Mineral Type | - | Aluminium Oxide |
| Adhesion to Steel | PSTC-4 | 1500 g/25.4mm ² |
| Tensile Strength | PSTC-31 | 6.0 kg/25.4mm ² |
| Tear Resistance | PSTC-39 | 5600g ± 200g |
| Elongation at Break | PSTC-31 | 25 % |
| Temperature Range | - | -40°C to +80°C |
| Resistance to Water | PSTC-35 | 10 Months |
| Resistance to Chemicals | PSTC-35 | 8 Months |
| Resistance to Motor Oil | PSTC-35 | Excellent |

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Technical Data Continued

| Property | Test Method | Value |
|---|------------------------|-----------------|
| Life Span | PSTC-9 | 12 to 24 Months |
| Maximum Size of Roll Production | - | 1168mm x 100m |
| Coefficient of Friction - Dry Surface | Pendulum EN 16165:2021 | 0.99 PTV |
| Coefficient of Friction - Wet Surface | Pendulum EN 16165:2021 | 0.80 PTV |
| Coefficient of Friction - Dry / Wet Surface | DIN 51130 | R13 |

Light Reflective Values

| Colour | RAL | Average LRV | Range |
|-----------------------|-------------|--------------|-------|
| Black | 9004 | 0 | 0 |
| Grey | 7045 | 17.1 | - |
| Yellow | 1023 | 38.25 | 3 |
| Green | 6010 | 1.5 | 5 |
| White | 9003 | 57.44 | 2.51 |
| Transparent | Transparent | 49.7 | - |
| Black / Yellow Hazard | 9004 / 1023 | 1.38 / 35.73 | - |

Approvals



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.