

Extra Coarse Safety Grip Tape

Product Code: RC3402-EC

Key Features

- 30 grit aluminium oxide extra coarse surface
- Designed for harsh environments and heavy use
- Suitable for snow, ice and muddy conditions
- High tack adhesive for difficult substrates
- Durable plastic film backing for heavy granules
- Deep grit channels aid drainage and prevent clogging
- Ideal for industrial and outdoor applications

Attributes



Anti-Slip



Durable



High Strength



Technical Data

Property	Test Method	Value
Applied Thickness (MIL D-17951)	Calipers	1.74mm
Flammability	BS 5438:1972 Test 2, BS5867: 1980 Part 2	4 Acceptances
Peel Adhesion	180° FINAT FTMI	17.9 N/25mm
Tensile Strength	Lloyd, 500N Load Cell	76.4 N/25mm
UV Resistance	Grey Scale Test	Good
Applied Weight	-	1255 g/m ²
Slip Resistance	DIN 51130 (ZH1/571)	R13
Coefficient of Friction - Dry Surface	ASTM C 1028-96 (Static Method) Pendulum (Dynamic Method)	1.33 102 TRL
Coefficient of Friction - Wet Surface	ASTM C 1028-96 (Static Method) Pendulum (Dynamic Method)	1.21 80 TRL
Minimum Application Temperature	-	+4° C
Working Temperature Range	-	-30° C to +70° C

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Technical Data Continued

Property	Test Method	Value
Adhesive Strength	-	33.0
Elongation at Break	PSTC-31	25 %
Resistance to Water	PSTC-35	10 Months
Resistance to Chemicals	PSTC-35	Excellent
Resistance to Motor Oil	PSTC-35	Excellent
Maximum Size of Roll Production	-	1168mm x 100m

Light Reflective Values

Colour	RAL	Average LRV	Range
Black	9004	0	0
Green	6004	0.6	0.9

Approvals



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.