

Removable Anti-Slip Tape

Product Code: RC3427

Key Features

- Removable adhesive for clean, residue-free removal
- Durable aluminium oxide anti-slip grit
- Strong hold without permanent bonding
- Suitable for smooth and sealed surfaces
- Reduces slip risks in temporary environments
- Maximum roll size: 1168mm x 100m
- Easy application and removal
- Ideal for temporary or semi-permanent use

Attributes



Anti-Slip



Durable



Technical Data

Property	Test Method	Value
Back Carrier	Calipers	0.1mm Polyvinyl Chloride + 0.01mm Polyethylene Terephthalate
Type of Adhesive	-	Solvent Acrylic
Mineral Type	-	Aluminium Oxide
Adhesion to Steel	PSTC-4	0.3 kg/25.4mm ²
Temperature Range	-	-5° C to +50° C
Maximum Size of Roll Production	-	1168mm x 100m
Resistance to Water	PSTC-35	Good
Life Span	PSTC-9	12 to 24 Months
Colour	-	Black, Yellow, Black / Yellow Hazard
Coefficient of Friction - Dry Surface	Pendulum	102 TRL
Coefficient of Friction - Wet Surface	Pendulum	71 TRL

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Light Reflective Values

Colour	RAL	Average LRV	Range
Black	9004	0.3	0.1
Yellow	1003	48.4	1.4
Black / Yellow Hazard	9004 / 1003	0.7 / 81.5	2 / 3

Approvals



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.