

Chemical Resistant Anti-Slip Tape

Product Code: RC3447

Key Features

- High-performance anti-slip tape for use in areas with high chemical exposure
- Exceptional chemical resistance
- Resistant to oils, solvents, and aggressive cleaning agents
- Ultra-thin 0.1mm profile
- Available in standard, coarse and extra coarse
- Roll widths from 19mm to 1168mm
- Suitable for indoor and outdoor use

Attributes



Chemical-Resistant



Anti-Slip



Durable



Technical Data

Property	Test Method	Value
Back Film	Calipers	0.1mm Polyvinyl Chloride
Type of Adhesive	-	Solvent Acrylic
Mineral Type	-	Aluminium Oxide
Adhesion to Steel	PSTC-4	1500 g/25.4mm ²
Tensile Strength	PSTC-31	6.0 kg/25.4mm ²
Tear Resistance	PSTC-39	5600g ± 200g
Elongation at Break	PSTC-31	25 %
Temperature Range	-	-30° C to +70° C
Maximum Size of Roll Production	-	1168mm x 100m
Resistance to Motor Oil	PSTC-35	Excellent
Colour	-	Black
Coefficient of Friction - Dry Surface	Pendulum	102 TRL
Coefficient of Friction - Wet Surface	Pendulum	71 TRL

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Light Reflective Values

Colour	RAL	Average LRV	Range
Black	9004	0	0

Approvals



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.